

10 スラストベアリング

品名	寸法 (mm)				Type	耐荷重 (kgf)		備考
	D	d	d'	B		Cr	Cor	
PCK12RSUS	12.0	6.2	6.2	4.5	1	54	66	ケースのみSUS
PCK12SUS	12.5	7.1	7.1	5.1	1	55	75	ケースのみSUS
PCK817R	17.0	8.1	8.1	8.0	3	93	100	リテーナ入り、ケースなし
PCK21	21.4	6.4	7.0	8.3	1	170	178	
PCK1122	21.8	11.5	12.1	7.1	1	132	205	
PCK22R	22.0	8.5	8.5	9.0	1	226	219	
PCK23	23.0	10.5	10.5	12.0	1	235	259	
PCK25	24.8	12.0	12.0	10.0	1	187	265	
PCK1225	25.4	12.7	13.3	8.7	1	253	338	
PCK26R新	26.0	12.0	12.0	8.5	1	242	304	
PCK26SUS	26.0	12.2	12.2	5.3	1	140	240	ケースのみSUS
PCK27	26.6	9.5	10.2	9.1	1	193	292	
PCK1327	27.6	13.2	13.2	9.5	1	198	321	
PCK1528	28.0	15.1	15.1	5.0	1	96	229	
PCK1628	28.0	16.0	16.0	9.0	1	201	352	
PCK1628C	28.6	15.9	16.7	8.7	1	201	352	
PCK35A	35.0	20.0	20.0	10.0	1	287	547	
PCK361	36.1	15.9	16.5	11.5	1	424	604	
PCK36	36.5	22.5	22.5	7.9	1	229	522	
PCK37	36.8	20.0	20.0	11.0	1	434	677	
PCK40K	40.0	17.0	-	12.0	2		649	
PCK2040	40.0	20.0	20.5	13.8	1	609	842	
PCK2543	43.0	25.0	25.0	10.0	1	318	752	
PCK3047	47.0	30.0	39.0	11.0	1	410	970	
PCK3248	48.0	31.9	31.9	9.5	1	332	878	

注：(1) 弊社製品は基本的に受注生産となっております。

(2) 耐荷重は弊社計算値です。

